

**ANTI-SALT SOLUTION** 

## ADDITIVE

## **FORALPROOF**



## FOR OLL

type of product: anti-humidity and anti-salt product in a watery solution.

characteristics: it is composed of a predispersion of silica and stabilizing silicone

derivates in a watery solution for blocking efflorescence and

against capillary-action rising damp.


substrates: old and new masonries with humidity problems.

FORKOLL FORALPROOF anti-humidity and anti-salt product for specifications:

old and new masonries.

alternative products:

none.







PACKAGING: plastic drums from 5 l to 16 l.	
apperance	viscose liquid
colour	transparent straw yellow
density	approx 1,060 Kg/d
PH	approx 13
solubility	total



## **RANGE OF USE:**

used for the treatment of old and new masonries with problems of humidity, efflorescence, and as anti-salt treatment before the application of dehumidifying plaster.

**PREPARING THE SUBSTRATE:** the substrates must be free from incoherent materials, grease, oils, wax and other substances which could compromise the product penetra-

PREPARING THE MIX: it is a ready-to-use product. Any added product could compromise solution stability and final result.

APPLYING THE MIX: apply the product only on dry or slightly damp surfaces, possibly in the shade, with roller, large brush or broom accordingly to the entity and shape of the surfaces. Apply the plaster as soon as the surface is dry or slightly damp.

CONSUMPTION: 0.200 l. per m² surface depending on the

substrate porosity.

**WARNING:** application temperature from +5°C to +35°C. Do not apply when it is very sunny or rainy. Do not add anything before using the product.