

FOR KOLL®

PRIMER

ADDITIVE

FOR X33



FOR KOLL®

type of product:

FOR X 33 is a product composed of high quality latex and selected fine-grained sands.

preparation:

easy to apply, exceptional strength bond on any dry and wet substrate.

characteristics:

degreaser for indoor and outdoor substrates with hard adhesion (smooth walls, grès, etc.).

dilution:

with drinking water 1-2%



PACKAGING: 17 l. plastic drums

colour	yellow 40
specific weight	1,50 g/cm ³
viscosity	40 Mpa*sp
dry solid content	58 %
appearance	emulsion
water solubility	miscible



RANGE OF USE:

degreaser for indoor and outdoor substrates with hard adhesion (smooth walls, grès, etc.).



APPLICATION: apply FOR X33 with a brush one or two coats depending on the surface absorption. Hardening time is of few hours in good weather conditions. It is advisable to wait until the product is completely hardened before proceeding to the next steps.

CONSUMPTION: 1 Kg per 2-3m² surface depending on the absorpency of the substrate.

WARNING: application temperature from +5°C to +35°C. Do not apply when it is very sunny or rainy. In case of tiles with very dusty backs they should be rapidly cleaned in water. Storage: 12 months in a dry place. Producer is not responsible for any consequences deriving from a wrong use of the product.